

1 2 3 4 5 6 7 8

SMA701-13.5 T124426000TU

品名: SMA PCB ジャック L=13.5mm

SMA701-13.5



Electrical

Impedance: $50\ \Omega$
 Frequency: DC-12.4GHz
 V.S.W.R: 1.19Max at 2.0GHz
 Insulation Resiatance: $5000M\ \Omega$ Minimum
 Contact Resistance:
 Center Coantact:: $4m\ \Omega$
 Outer Contact: $3m\ \Omega$
 Insulator Withstanding Voltage: 750VRMS

Mechanical

- ① Body: Brass Gold Finish $5\ \mu$ Inch
 - ② Center contact: Be Cupper, Gold Finish $30\ \mu$ Inch
 - ③ Insulater: Teflon
 - ④ Fellule: Brass Gold finish $5\ \mu$ Inch
- Brass Material: $Cd < 75ppm$, $Pb < 40,000ppm$
 RoHs Regulation: Comply
 Dulability: 500cycles

未記入公差

長度公差: ± 0.08
 直徑公差: ± 0.03

尺度

單位
mm

TAKITEK

タキテック株式会社

製品名
SMA PCB Jack 13.5

部品名
T124 426 000

△	- -		
△	- -		
△	- -		
△	- -		
△	- -		
△	- -		

F